Amendments to the claims:

This listing of claims will replace all prior versions and listing of claims in the application.

Listing of Claims:

1

- (Currently Amended) A field grading material comprising: a polymer matrix, said polymer matrix having two or more polymer phases; and a field grading effective amount of a semiconducting nanoparticle filler, wherein said
- filler is heterogeneously distributed in said polymer matrix such that said semiconducting nanoparticle filler is well dispersed in at least part of one of said polymer phases; and wherein said semiconducting nanoparticle filler comprises less than 40% by volume of said field grading material
- 2. (Previously Presented) A field grading material according to claim 1, wherein said nanoparticle filler is selected from semiconducting materials having an energy bandgap ranging from 0 eV to 5 eV and dielectric materials having a bulk dielectric constant at infinitely high frequencies of at least 5.
- 3 (Previously Presented) A field grading material according to claim 1, wherein said nanoparticle filler comprises a semiconducting material.
- (Previously Presented) A field grading material according to claim 1, wherein said nanoparticle filler is selected from ZnO, SnO, InO, CeO, TiO2, SiC, BaTiO3, Al2O3, SiO2 and mixtures thereof.
- 5 (Previously Presented) A field grading material according to claim 1, wherein said polymeric matrix comprises a rubber, a thermoplastic polymer, a thermosetting polymer, or thermoplastic elastomer.

- (Previously Presented) A field grading material according to claim 5, wherein said
 polymeric matrix comprises at least one of a polyolefin rubber, a thermoplastic polyolefin
 clastomer, a silicone rubber, and a crystalline thermoplastic polymer.
- (Previously Presented) A field grading material according to claim 5, wherein said polymeric matrix comprises a polymer selected from EPDM and polyethylene.
- (Previously Presented) A field grading material according to claim 1, wherein said polymeric matrix comprises a polymer blend of immiscible polymers.
- (Previously Presented) A field grading material according to claim 8, wherein said polymer blend is selected from polyethylene/EPDM, LDPE/HDPE, and maleic anhydridemodified EPDM/EPDM.
- (Previously Presented) A field grading material according to claim 1, wherein said nanoparticles have a particle size from 2 to 80 nm.
- 11. (Previously Presented) A field grading material according to claim 1, wherein said nanoparticle filler comprises less than 30% by volume of the field grading material.
- 12. (Previously Presented) A field grading material according to claim 1, wherein a surface of said nanoparticle filler is modified by treatment with a organosilane or organotitanate compound and the organosilane compound comprises an organic group selected from alkyl, alkylamino, amino and carboxy.
- (Previously Presented) A field grading material according to claim 12, wherein said organic group is selected from methyl, decyl, octyl, vinyl, aminopropyl and acetoxy.
- 14. (Currently Amended) A field grading material comprising a <u>semiconducting</u> nanoparticle filler heterogeneously distributed in a polymeric matrix, wherein a surface of said <u>semiconducting</u> nanoparticle filler is modified by treatment with an organosilane or

organotitanate compound and said organosilane compound comprises an organic group selected from alkyl, alkylamino, amino and carboxy.

- (Previously Presented) A field grading material according to claim 14, wherein said organic group is selected from methyl, deeyl, octyl, vinyl, aminopropyl, and acetoxy.
- (Canceled).
- 17. (Canceled).
- 18. (Previously Presented) A method for reducing electric field stress at a joint or termination of an electric cable, said method comprising introducing in said joint or termination a field grading material according to claim 1.
- 19. (Withdrawn) An insulating material comprising an insulating effective amount of a nanoparticle filler distributed in a polymeric matrix, wherein said nanoparticle filler is heterogeneously distributed in said polymeric matrix.
- 20. (Withdrawn) An insulating material according to claim 19, wherein said_nanoparticle filler is selected from semiconducting materials having an energy bandgap ranging from 0 eV to 5 eV and dielectric materials having a bulk dielectric constant at infinitely high frequencies of at least 5.
- (Withdrawn) An insulating material according to claim 19, wherein said_nanoparticle filler comprises a semiconducting material.
- (Withdrawn) An insulating material according to claim 19, wherein said nanoparticle filler is selected from ZnO, SnO, InO, CeO, TiO₂, SiC. BaTiO₃, Al₂O₃, SiO₂ and mixtures thereof.
- 23. (Withdrawn) An insulating material according to claim 19, wherein said polymeric matrix comprises a rubber, a thermoplastic polymer, a thermosetting polymer, or thermoplastic elastomer.

- 24. (Withdrawn) An insulating material according to claim 23, wherein said polymeric matrix comprises at least one of a polyolefin rubber, a thermoplastic polyolefin elastomer, a silicone rubber, and a crystalline thermoplastic polymer.
- (Withdrawn) An insulating material according to claim 23, wherein said polymeric matrix comprises a polymer selected from EPDM and polyethylene.
- (Withdrawn) An insulating material according to claim 19, wherein said polymeric matrix comprises a polymer blend of immiscible polymers.
- (Withdrawn) An insulating material according to claim 26, wherein said polymer blend
 is selected from polyethylene/EPDM, LDPE/HDPE, and maleic anhydride-modified
 EPDM/EPDM.
- 28. (Withdrawn) An insulating material according to claim 19, wherein said nanoparticles have a particle size in at least one of a range from 2 to 80 nm, from 5 to 50 nm, and from 5 to 30 nm
- 29. (Withdrawn) An insulating material according to claim 19, wherein said nanoparticle filler comprises less than 20% by volume of the insulating material, less than 10% by volume of the insulating material, or less than 5% by volume of the insulating material.
- 30. (Withdrawn) An insulating material according to claim 19, wherein a surface of said nanoparticle filler is modified by treatment with an organosilane or organotitanate compound and said organosilane compound comprises an organic group selected from alkyl, alkylamino, amino and carboxy.
- (Withdrawn) An insulating material according to claim 30, wherein said organic group is selected from methyl, decyl, octyl, vinyl, aminopropyl and acetoxy.
- (Withdrawn) An insulating material comprising a nanoparticle filler distributed in a
 polymeric matrix, wherein a surface of said nanoparticle filler is modified by treatment with an

organosilane or organotitanate compound and said organosilane compound comprises an organic group selected from alkyl, alkylamino, amino and carboxy.

- (Withdrawn) An insulating material according to claim 32, wherein the organic group is selected from methyl, decyl, octyl, vinyl, aminopropyl and acetoxy.
- 34. (Withdrawn) An insulating material comprising a carbon nanotube filler distributed in a polymeric matrix, wherein said filler is heterogeneously distributed in said polymeric matrix and said polymeric matrix comprises a rubber, a thermoplastic polymer, a thermosetting polymer, thermoplastic elastomer or a crystalline thermoplastic polymer.
- (Withdrawn) An insulating material according to claim 34 wherein a polymeric matrix comprises a polymer selected from EPDM and polyethylene.
- 36. (Withdrawn) A process for manufacturing a field grading material, said process comprising:

mixing a nanoparticle filler with at least one polymer to form a mixture, wherein said polymer is in a particulate form, said polymer particulates being at least 10 times greater in size than said nanoparticle filler, and said polymer comprises a rubber, a thermoplastic polymer, a thermosetting polymer, or a thermoplastic elastomer; and

heating said mixture to form said field grading material.

- (Withdrawn) A process according to claim 36, wherein said at least one polymer comprises a mixture of immiscible polymers.
- 38. (Withdrawn) A process according to claim 36, wherein said polymer is selected from a group consisting of polyolefin rubber, a thermoplastic polyolefin elastomer, a silicon rubber, and a crystalline thermoplastic polymer.
- (Withdrawn) A process according to claim 36, wherein said polymer is selected from EPDM and polyethylene.

- 40. (Withdrawn) A process according to claim 36, wherein said polymer particulates are at least 100 times greater in size than the nanoparticle filler.
- 41. (Withdrawn) A process according to claim 36, wherein said polymer particulates are at least 1000 time greater in size than the nanoparticle filler.
- (Withdrawn) A process according to claim 36, wherein said nanoparticle filler is semiconducting carbon nanotubes.